

COMPACT, LIGHT WEIGHT DESIGN, 3 INCH PORTABLE PRINTER

LK-P31

- Light weight (310g with battery) & robust durable structure
- Compact size : 110(W) X 105(D) X 30(H) mm
- Drop resistance : 1.2M onto concrete
- Prints at 60mm per second
- Equipped power options AC/DC charger and vehicle charger(12/24V)
- Various O/S drivers : Windows Printer Driver (7, XP, 2000, 2003, VISTA, 32 & 64bit), Windows(CE 4.2 & 5.0 / Mobile 5.0-), Linux Printer Driver, Symbian, Blackberry, Android (2.1-)



SPECIFICATION

PRINT METHOD		Direct Thermal
PRINTING SPEED (max)		60mm/sec
DOT DENSITY		203 DPI
DOT PITCH		8dots /mm, 0.125pitch
EFFECTIVE PRINTING WIDTH		72mm, 576dots/line
PAPER	TYPE	Thermal paper
	WIDTH	79.5mm ± 0.5mm
	THICKNESS	0.06~0.09mm
	ROLL DIAMETER	Max. ø 25mm ± 0.5mm
	ROLL CORE INNER DIAMETER	8.5mm ± 0.5mm
RELIABILITY	TPH LIFE	50km
	PULSE ACTIVATION	50,000,000pulse or more
BARCODE	EAN-8, EAN-13, Code 39, ITF, UPC-A, UPC-E, Codabar, Code 93, Code 128, PDF 417(2D), QR Code(2D)	

EMULATION	ESC/POS Command compatible	
DRIVER	Windows Printer Driver(7, XP, 2000, 2003, VISTA, 32 & 64bit), Windows(CE 4.2 & 5.0 / Mobile 5.0-), Linux Printer Driver, Symbian, Blackberry, Android (2.1-)	
SENSOR	Paper end / Black mark / Cover open sensors	
INTERFACE	USB, Bluetooth class 2	
BATTERY CHARGER	External Charger (Output 8.4VDC/0.8A)	
BATTERY	7.4V 1130mAh Li-ion, 2Hrs Charging Time, 10Hrs stand-by	
DIMENSION	WxDxH(mm)	110 x 105 x 30
	WxDxH(inch)	4.33 x 4.13 x 1.18
WEIGHT	310g(with Battery)	
TEMPERATURE	OPERATION	-10 ~ 50°C
	STORAGE	-20 ~ 60°C
HUMIDITY	OPERATION	35 ~ 95%
	STORAGE	10 ~ 95%

